

Declaration of performance (DOP)

No. 9174 056 DOP 2013-06-17

1. Unique identification code of the product-type:

Single wall chimney system type EW-TITAN-ALBI according to EN 1856-1:2009

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Single wall chimney system type EW-TITAN-ALBI, installation in stack¹⁾

Model 1 DN (60- 600) T200 – P1 – W – V2 – L99050 – O00

Model 2 DN (60- 600) T200 – N1 – W – V2 – L99050 – O00

¹⁾ Manufacturer product identification EW-TITAN-ALBI

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Convey the products of combustion from heating appliances to the outside atmosphere

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Jeremias GmbH**
Opfenrieder Straße 11-14
DE-91717 Wassertrüdingen
Tel.: +49 9832 68 68 0
Fax: +49 9832 68 68 68
Email: info@jeremias.de

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+ and System 4

7. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Notified factory production control certification body no. 0036 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity 0036 CPD 9174 056 of the factory production control.

8. Declared performance:

	Essential Characteristics	Performance	Harmonized technical specification																								
8.1	Compressive strength Chimney sections, fittings and supports	<u>Sections and fittings:</u> Model 1 DN (60- 600): up to 10 m Model 2 DN (60- 600): up to 10 m <u>Supports:</u> n.p.d. For further information see the installation instruction EW-TITAN-ALBI	EN 1856-1:2009																								
8.2	Resistance to fire	(Resistance to fire from inside to outside) Model 1 to 2 DN (60- 600): T200 – O00 Tested without cover, with back ventilated ceiling duct	EN 1856-1:2009																								
8.3	Gas tightness/ leakage	Model 1 DN (60- 600): P1 Model 2 DN (60- 600): N1	EN 1856-1:2009																								
8.4	Flow resistance of chimney sections fittings and terminals	According to EN 13384-1 <table border="1" data-bbox="566 795 1173 1205"> <thead> <tr> <th>component:</th> <th>ζ (Zeta-value) single resistances</th> </tr> </thead> <tbody> <tr> <td>pipe tee 87°:</td> <td>1,14</td> </tr> <tr> <td>pipe tee 45°:</td> <td>0,35</td> </tr> <tr> <td>pipe bend 87°:</td> <td>0,40</td> </tr> <tr> <td>pipe bend 45°:</td> <td>0,28</td> </tr> <tr> <td>pipe bend 30°:</td> <td>0,20</td> </tr> <tr> <td>pipe bend 15°:</td> <td>0,10</td> </tr> <tr> <td colspan="2">Terminals: (only for operation in negative pressure)</td> </tr> <tr> <td>rain cap</td> <td>1,0</td> </tr> <tr> <td>fin cap type „Hubo“:</td> <td>$\leq \varnothing 140 \text{ mm } 0,1 / \geq \varnothing 150 \text{ mm } 0,2$</td> </tr> <tr> <td>wind deflector:</td> <td>$\leq \varnothing 140 \text{ mm } 0,1 / \geq \varnothing 150 \text{ mm } 0,2$</td> </tr> <tr> <td>hurricane:</td> <td>0,1</td> </tr> </tbody> </table>	component:	ζ (Zeta-value) single resistances	pipe tee 87°:	1,14	pipe tee 45°:	0,35	pipe bend 87°:	0,40	pipe bend 45°:	0,28	pipe bend 30°:	0,20	pipe bend 15°:	0,10	Terminals: (only for operation in negative pressure)		rain cap	1,0	fin cap type „Hubo“:	$\leq \varnothing 140 \text{ mm } 0,1 / \geq \varnothing 150 \text{ mm } 0,2$	wind deflector:	$\leq \varnothing 140 \text{ mm } 0,1 / \geq \varnothing 150 \text{ mm } 0,2$	hurricane:	0,1	EN 1856-1:2009
component:	ζ (Zeta-value) single resistances																										
pipe tee 87°:	1,14																										
pipe tee 45°:	0,35																										
pipe bend 87°:	0,40																										
pipe bend 45°:	0,28																										
pipe bend 30°:	0,20																										
pipe bend 15°:	0,10																										
Terminals: (only for operation in negative pressure)																											
rain cap	1,0																										
fin cap type „Hubo“:	$\leq \varnothing 140 \text{ mm } 0,1 / \geq \varnothing 150 \text{ mm } 0,2$																										
wind deflector:	$\leq \varnothing 140 \text{ mm } 0,1 / \geq \varnothing 150 \text{ mm } 0,2$																										
hurricane:	0,1																										
8.5	Thermal resistance	Model 1 to 2 DN (60- 600): 0 m²K/W tested at 200°C (without insulation) >0,26 m²K/W tested at 200°C (with 25 mm insulation) 0,501 m²K/W tested at 200°C (with 32 mm insulation)	EN 1856-1:2009																								
8.6	Thermal shock resistance Sootfire resistance	Model 1 to 2 DN (60- 600): No²⁾ ²⁾ because designated O	EN 1856-1:2009																								
8.7	Thermal performance under normal operating conditions	Model 1 to 2 DN (60- 600): T200																									
8.8	Flexural tensile strength (only for means of connection for chimney sections and fittings)	Model 1 DN (60- 600): n.p.d. Model 2 DN (60- 600): n.p.d.	EN 1856-1:2009																								
8.9	Non vertical installation	Model 1 to 2 DN (60- 600): Maximum offset between supports 4 m at 90° (inclined run, maximum distance between two fixations, supports at non vertical installation)	EN 1856-1:2009																								
8.10	Components subject to wind load	Model 1 to 2 DN (60- 350): 1,5 m (locking band necessary) Model 1 to 2 DN (>350- 600): n.p.d.	EN 1856-1:2009																								

8. Declared performance:

	Essential Characteristics	Performance	Harmonized technical specification
8.11	Durability: Water and vapour diffusion resistance	Model 1 to 2 DN (60- 600): Yes	EN 1856-1:2009
8.12	Condensate penetration resistance	Model 1 to 2 DN (60- 600): Yes	
8.13	Against corrosion	Model 1 to 2 DN (60- 600): V2	
8.14	Freeze thaw resistance	Model 1 to 2 DN (60- 600): Yes	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Wassertrüdingen, 17th June 2013



.....
Stefan Engelhardt CEO

Product information

“Chimneys - Requirements for metal chimneys - Part 1:
System chimney products” DIN EN 1856-1:2009

Manufacturer’s identification:

jeremias GmbH
Opfenrieder Str. 11-14
91717 Wassertrüdingen
 Tel.: +49 (0) 9832 / 68 68-50
 Fax: +49 (0) 9832 / 68 68-68
 Internet: www.jeremias.de
 E-Mail: info@jeremias.de

Product trade name:

EW-TITAN-ALBI (Single wall chimney system, installation in stack)

Certification office:

TÜV SÜD Industrie Service GmbH

Name and position of the responsible person:

Stefan Engelhardt CEO 

Identification of accompanying documentation

0.1	Metal chimney	EN 1856-1	T200	P1	W	V2-L99050	O(00)	60 – 600	Single wall chimney system, moisture resistant, for installation in stacks / chimneys, which meet the requirements for fire protection. Installation with rear ventilation. Operation mode in positive pressure.
0.2	Metal chimney	EN 1856-1	T200	N1	W	V2-L99050	O(00)	60 – 600	Single wall chimney system, moisture resistant, for installation in stacks / chimneys, which meet the requirements for fire protection. Operation mode in negative pressure.

Product description	
Standard number	EN 1856-1
Temperature level	T200
Pressure level	P1
Condensate resistance (W: wet / D: dry)	W
Corrosion resistance	V2-L99050
Flue liner material specification	O(00)
Sootfire resistance (G: yes / O: no) and distance to combustible material (in mm)	60 – 600
Nominal diameter (Ø) (inner tube) in mm	

Properties of a single wall metal chimney system

Pressure resistance:

Maximum load (see encl. H-1 Installing instructions)

Flow resistance:

Average roughness: 1,0 mm, Zeta-values according to DIN EN 13384-1 (see encl. H-1 Installing instructions)

Thermal resistance in stack

Without insulation 0 m²K/W
 Optional with 25 mm insulation >0,26m²K/W
 or 32 mm insulation 0,501m²K/W

Flexural strength:

Angular assembly: Maximum length
 between two supports: 4 m at 90°

Freeze-thaw resistance:

Yes

Cleaning:

The chimney system is only allowed to be
 cleaned with cleaning devices made of plastic
 or rust-resistant stainless steel.