

Declaration of performance (DOP)

No. 9174 058 DOP 2013-06-17

1. Unique identification code of the product-type:

Rigid metal connecting pipe type EW-TITAN-ALBI & EW-TITAN-ALB according to EN 1856-2:2009

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

**Single wall connecting pipe type EW-TITAN-ALBI & EW-TITAN-ALB
with gasket for positive pressure¹⁾**

Model 1 DN (60- 600) T200 – P1 – W – V2 – L99050 – O50 M³⁾

Model 2 DN (60- 600) T200 – N1 – W – V2 – L99050 – O50 M³⁾

¹⁾ Manufacturer product identification

²⁾ Not Measured (NM) means 3 times the Nominal Diameter with a minimum of 375 mm

³⁾ Measured (M)

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Convey the products of combustion from heating appliances to the chimney

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Jeremias GmbH**
Opfenrieder Straße 11-14
DE-91717 Wassertrüdingen
Tel.: +49 9832 68 68 0
Fax: +49 9832 68 68 68
Email: info@jeremias.de

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not applicable


6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Notified factory production control certification body no. 0036 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity 0036 CPD 9174 058 of the factory production control.

8. Declared performance:

	Essential Characteristics	Performance	Harmonized technical specification														
8.1	Compressive strength	Model 1 to 2 DN (60- 600): up to 10 m	EN 1856-2:2009														
8.2	Tensile strength	Model 1 to 2 DN (60- 600): n.p.d.															
8.3	Non vertical installation	Model 1 to 2: Horizontal 3 m between supports* *Please pay attention to the mounting instructions, an incline, all incline has to be arranged for where applicable.															
8.4	Resistance to fire	Model 1 to 2 DN (60- 600): O50 NM	EN 1856-2:2009														
8.5	Gas tightness/ leakage	Model 1 DN (60- 600): P1 Model 2 DN (60- 600): N1	EN 1856-2:2009														
8.6	Flow resistance of chimney sections and fittings	According to EN 13384-1 <table border="1" data-bbox="592 734 1201 992"> <thead> <tr> <th>component:</th> <th>ζ (Zeta-value) single resistances</th> </tr> </thead> <tbody> <tr> <td>pipe tee 87°:</td> <td>1,14</td> </tr> <tr> <td>pipe tee 45°:</td> <td>0,35</td> </tr> <tr> <td>pipe bend 87°:</td> <td>0,40</td> </tr> <tr> <td>pipe bend 45°:</td> <td>0,28</td> </tr> <tr> <td>pipe bend 30°:</td> <td>0,20</td> </tr> <tr> <td>pipe bend 15°:</td> <td>0,10</td> </tr> </tbody> </table>	component:	ζ (Zeta-value) single resistances	pipe tee 87°:	1,14	pipe tee 45°:	0,35	pipe bend 87°:	0,40	pipe bend 45°:	0,28	pipe bend 30°:	0,20	pipe bend 15°:	0,10	EN 1856-2:2009
component:	ζ (Zeta-value) single resistances																
pipe tee 87°:	1,14																
pipe tee 45°:	0,35																
pipe bend 87°:	0,40																
pipe bend 45°:	0,28																
pipe bend 30°:	0,20																
pipe bend 15°:	0,10																
8.7	Sootfire resistance	Model 1 to 2 DN (60- 600): No²⁾ ²⁾ because designated O	EN 1856-2:2009														
8.8	Thermal performance under normal operating conditions	Model 1 to 2 DN (60- 600): T200* *(Heating strain at nominal operating temperature)															
8.9	Durability: Water and vapour diffusion resistance	Model 1 to 2 DN (60- 600): Yes	EN 1856-2:2009														
8.10	Condensate penetration resistance	Model 1 to 2 DN (60- 600): Yes															
8.11	Against corrosion	Model 1 to 2 DN (60- 600): V2															
8.12	Freeze thaw resistance	Model 1 to 2 DN (60- 600): Yes															
<p>9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.</p> <p>Signed for and on behalf of the manufacturer by:</p> <p>Wassertrüdingen, 17th June 2013</p> <div style="text-align: right;">  Stefan Engelhardt CEO </div>																	

Product information

“Chimneys - Requirements for metal chimneys - Part 2:
Metal flue liners and connecting flue pipes” DIN EN 1856-2:2009

Manufacturer's identification:

jeremias GmbH
Opfenrieder Str. 11-14
91717 Wassertrüdingen
Tel.: +49 (0) 9832 / 68 68-50
Fax: +49 (0) 9832 / 68 68-68
Internet: www.jeremias.de
E-Mail: info@jeremias.de

Product trade name:

EW-TITAN-ALBI & EW-TITAN-ALB Connecting pipe
(single wall connecting pipe for positive pressure with joint seals)

Certification office:

TÜV SÜD Industrie Service GmbH

Name and position of the responsible person:

Stefan Engelhardt CEO 

Identification of accompanying documentation

Single wall connecting pipe EW-TITAN-ALBI & EW-TITAN-ALB	0.1	EN 1856-2	T200	P1	W	V2-L99050	O50 M	60 - 600	Single wall connecting pipe, moisture resistant, composed of rigid pipes and elements with lip gaskets (albi) or outer gaskets (alb), ventilated along the whole length, without covering. Operation mode in positive pressure up to 200 Pa (oil, gas).
	0.2	EN 1856-2	T200	N1	W	V2-L99050	O50 M	60 - 600	Single wall connecting pipe, moisture resistant, composed of rigid pipes and elements with lip gaskets (albi) or outer gaskets (alb), ventilated along the whole length, without covering. Operation mode in negative pressure (oil, gas).

Product description	
Standard number	EN 1856-2
Temperature level	T200
Pressure level	P1
Condensate resistance (W: wet / D: dry)	W
Corrosion resistance	W
Flue liner material specification	V2-L99050
Sootfire resistance (G: yes / O: no) and distance to com- bustible material (in mm)	O50 M
M = tested distance NM = calculated distance	
Nominal diameter (Ø) inner tube in mm	60

Rigid connecting pipe of metal

Compressive strength:

>10 m over the modules and the connections of the elements

Coefficient for flow resistance:

Average roughness: 1,0 mm, Zeta-values according to DIN EN 13384-1

Thermal resistance:

0 m²K/W without insulation

Flexural strength:

No vertical installation: ≤ 3 m between two brackets, supports or fixations.

Tensile strength:

n.p.d.

Maximal distance between vertical supports:

≤ 4 m

Freeze-thaw resistance:

Yes

Cleaning:

The connecting pipe is only allowed to be cleaned with cleaning devices made of plastic or rust-resistant stainless steel.